

MS25-10



COM_ETISTORE_IDENT_SPECIFICATIONS

ETI Code	004600100
Description	MS25-10
Class name	Mot.protec.circuit breaker
Rated operation power at AC3 (kW)	3...4
Current setting range (A)	6,3 - 10
Short-circuit release I _{rm} (A)	110
Max. rated operational voltage (V AC)	690
Max. rated operational voltage (V AC)	690

Online product page [🔗](#)

Other documentation



[COM_ETISTORE_DOCTYPE_TD](#)
[COM_ETISTORE_DOCTYPE_3DFile](#)
[COM_ETISTORE_DOCTYPE_declaration](#)



ETIM international clasification

Classification	EC000074
Class name	Mot.protec.circuit breaker
Adjustment range undelayed short-circuit release	6,3A
Degree of protection (IP)	IP20
Number of poles	3
Overload release current setting	10A
Phase failure sensitive	1
Rated operating voltage	400V
Rated operation power at AC-3, 230 V	3...4kW
Rated operation power at AC-3, 400 V	3...4kW
Switch off technique	Thermomagnetic
Type of control element	Push button
Type of electrical connection of main circuit	Screw connection
With integrated auxiliary switch	1
With integrated under voltage release	1

COM_ETISTORE_dimension

